

VITA-D-CHLOR™

Use the best dechlorination chemical with the best dechlorination devices.

LPD-250 Diffusing Dechlorinator

Performance Data

Chlorine Levels

0–10 ppm

Flush Rate

200–1,250 gpm

Setup Time

1–3 mins.

Procedure (Treatment up to 5 ppm chlorine)

1. Setup the LPD on the hydrant
2. Put Stainless Steel Vita-D-Chlor Tablet Screen in the tablet chamber
3. Place 4 Vita-D-Chlor Tablets into the Tablet Screen
4. Flush and Test for complete dechlorination

Benefits/Features

- Simple, Low Cost
- Durable construction
- Dissipates/diffuses discharge water
- Utilizes tablets for simplified operations
- Tablets contained within the device; No connections to an external chemical source
- Traps debris in the discharge
- Accepts Pitot for flow measurement
- Connects directly to hydrant or hose extension
- No pre-flush solution mixing



LPD-250 Diffusing Dechlorinator Tablet System

VITA-D-CHLOR™

- NSF Granular
- One gram neutralizes 100 gallons of water with 1 ppm chlorine
- Soluble
- Safe for operators & the environment

AVAILABLE UNIT SIZES:

- 2.5 kg
- 12 kg
- 25 kg resealable poly pails

VITA-D-CHLOR™ Neutral

- NSF Granular
- pH Neutral
- Very Soluble
- Safe for operators & the environment

AVAILABLE UNIT SIZES:

- 2.5 kg
- 12 kg
- 25 kg resealable poly pails

VITA-D-CHLOR™ Tablets

- 2.5 inch tablet
- Easy to use
- 100% organic and water soluble
- Safe for operators & the environment

AVAILABLE UNIT SIZES:

- 20 tablets
- 40 tablets
- 35 lb (approx. 140 tablets)



■ Phone 800.322.6646 ■ Website www.Vita-D-Chlor.com